Valuable Features:

- Designed with uptime in mind, ease of maintenance.
- Complies to all international required standards to ensure safe and efficient operation.
- Minimal energy input requirement to support conservation farming and reduce the cost of spraying.
- High quality polyethylene tank ensures long lasting usage.
- Simple and accurate calibration to support improved efficiency and reduce losses.

Evenflow Turret:

The Evenflow Turret is a bolt on attachment on both Orchard and Citrus sprayers and constructed of stainless steel.

The turret is equipped with 12 double rollover nozzle bodies on both sides.

The air momentum and air velocity profiles are designed to achieve maximum recovery of the active ingredient on the target, and minimize variation of deposition on the target. The Evenflow technology optimises the energy requirement balance.

The Evenflow Turret kit draws its name from its ability to achieve a spray distribution, from the ground to tree top and left to right tree row with minimal variance.





Information:

AFGRI Vineyard Sprayer 1000L | 1500L

	1000L	1500L				
Rinse tank	90L	116.1L	Fan pitch	Adjustable	Turrets nozzles	N/A
Track width (m)	1.25 - 1.55	1.35 -1.65	Hand wash tank	15.8L	Drawbar	Adjustable
Tires	225/75R15	10.0/75R15.3	Pump	Comet APS121, 120L	Chassis	Galvanized
Controls	Manual	Electric	Pressure	50 bar		
Fan size	800 mm		Power required	35 kW	Easy access service system	NA
Fan capacity	21 000 m³ (L) 26 000 m³ (H)		Turret Evenflow	N/A	Service System	

AFGRI Citrus Sprayer 2000L | 3000L

	2000L	3000L				
Rinse tank	116,4L	234L	Fan pitch	Adjustable	Turret Evenflow	STD
Track width (m)	1.45 -1.75	1.65 - 1.95	Hand wash tank	15.8L	Turrets nozzles	22 Nozzles
Power required	55 kW	60 kW	Pump	Imovilli P306 Piston	Drawbar	Adjustable
Controls	Electric			Pump, 285L/min	Chassis	Galvanized
Fan size	940 mm		Pressure	50 bar	Easy access	STD
Fan capacity	36 200 m³ (L) 48 200 m³ (H)		Tires	10.5/80R18	service system	

AFGRI Orchard Sprayer 1500L | 2000L | 3000L

	1500L	2000L	3000L			
Track width (m)	1.35-1.65 1.45-1.75 1.65		1.65-1.95	Fan pitch	Adjustable	
Tires	10.0/75R15.3	10.0/75R15.3	10.5/80R18	Hand wash tank	15,8L	
Power required	45 kW	45 kW	50 kW	Pump	Comet APS-145 Pump, 145L	
Rinse tank	116L			Pressure	50 bar	
Controls	Electric			Fan size	940 mm	
Fan capacity	26 000 m³ (L) 36 000 m³ (H)			Easy access service system	STD	
Turrets nozzles	22 Nozzles					
Drawbar	Adjustable			Turret Evenflow	Optional	
Chassis	Galvanized					